

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number  
WO 2005/091924 A3

(51) International Patent Classification<sup>7</sup>: G01M 3/26

(21) International Application Number:  
PCT/US2005/006673

(22) International Filing Date: 2 March 2005 (02.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/550,415 5 March 2004 (05.03.2004) US

(71) Applicant (for all designated States except US): WATERS INVESTMENTS LIMITED [US/US]; 109 Lukens Drive, New Castle, DE 19720 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): CIOLKOSZ, Theodore, D. [US/US]; 362 Adams Street, Milton, MA 02186 (US). USOWICZ, James, E. [US/US]; 4A Street, Douglas, MA 01516 (US). BEALS, Peyton, C. [US/US];

90 Forestgrove Avenue, Wrentham, MA 02093 (US). KEENE, Russell [US/US]; 66 Beechwood Avenue, Sudbury, MA 01776 (US).


(74) Agent: JANIUK, Anthony, J.; Waters Corporation, 34 Maple Street, Milford, MA 01757 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: PRESSURE MONITOR OPTIMIZATION OF FLUID PATH UTILIZATION



(57) Abstract: A device comprising a pressure monitor and a control means that receives a signal representing measured pressure at the pressure monitor and controls the controllable elements of a fluid system is utilized to monitor a fluid system for error conditions, to optimize operations and to diagnose the fluid system. By following a testing protocol that selectively enables parts of the system, the control means narrows the list of possible failing components. Comparing the measured pressure against normal pressures allows the device to identify error conditions. Determining the volume of fluid being transported and controlling the duration of the flow optimizes operation of the fluid system.

WO 2005/091924 A3



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

**(88) Date of publication of the international search report:**

10 November 2005